

# UNDER HOIST TRANSMISSION JACKS

## for automotive use

**MODEL 57250 IMPORT** - Telescopic 1/2 Ton Capacity Single Pump

### INTENDED USE

Designed for the removal, installation and transportation (in the lowered position) of transmissions and transfer cases on passenger cars, vans, and light trucks that are raised by an in-ground or above-ground lift

### FEATURES

- Fully adjustable universal saddle with hand adjustable corner brackets and safety chain.
- Safety overload systems prevents jack from being used beyond its rated capacity.
- Foot operated pump and lowering pedals allow use of both hands to position and align saddle with transmission.
- Two-stage flash chromed rams inhibit rust from entering hydraulic system.
- Wide base with four easy rolling 4" diameter swivel ball bearing casters wheels, provide stability and easy maneuvering.
- Polyurethane wheels provide protection for tile and epoxy floors.

**OPTIONAL ADAPTERS AND SADDLES ON PAGE 3 AND 4**  
**Models 57204, 57209, 57210**



MODEL NUMBER	CAPACITY	LIFT RANGE		BASE SIZE	SADDLE TILT			SHIPPING WEIGHT (LBS)
		LOW	HIGH		Fwd	Back	Side	
<b>57250</b> <i>Single Pump</i>	1/2 TON	35"	72"	34" x 37"	42°	46°	± 12°	176
<b>57255</b> <i>Double Pump</i>	1/2 TON	35"	72"	34" x 37"	42°	46°	± 12°	178

**MODEL 57255 IMPORT** - Telescopic 1/2 Ton Capacity Double Pump

### INTENDED USE

Designed for the removal, installation and transportation (in the lowered position) of transmissions and transfer cases on passenger cars, vans, and light trucks that are raised by an in-ground or above-ground lift

### FEATURES

- Fully adjustable universal saddle with hand adjustable corner brackets and safety chain.
- Safety overload systems prevents jack from being used beyond its rated capacity.
- Foot operated pump and lowering pedals allow use of both hands to position and align saddle with transmission.
- Two-stage flash chromed rams inhibit rust from entering hydraulic system.
- Wide base with four easy rolling 4" diameter swivel ball bearing casters wheels, provide stability and easy maneuvering.
- Two times faster rising action as model 57250 with no load or a load up to 400 pounds.
- Same rising action as model 57250 for loads between 400 and 1,000 pounds.
- Polyurethane wheels provide protection for tile and epoxy floors.

**OPTIONAL ADAPTERS AND SADDLES ON PAGE 3 AND 4**  
**Models 57204, 57209, 57210**

